

<u>Meter size</u>	<u>Chamber Capacity</u>	<u>Bore Size</u>	<u>Pipe Size</u>	<u>Meter thread</u>	<u>Coupling Nut</u>	<u>Coupling Swivel</u>
1/2"x1/2"	15 gpm	1/2"	1/2"	1/2" external straight	1/2" internal straight	1/2" external pipe
5/8"x1/2"	20gpm	5/8"	1/2"	1/2" external straight	1/2" internal straight	1/2" external pipe
5/8"x3/4"	20gpm	5/8"	3/4"	3/4" external straight	3/4" internal straight	3/4"external pipe
3/4"x3/4"	30gpm	3/4"	3/4"	3/4"external straight	3/4"internal straight	3/4" external pipe
3/4"x1"	30gpm	3/4"	3/4"	1" external straight	1" internal straight	1" external pipe
1"	50gpm	1"	1"	1" external straight	1" internal straight	1" external pipe
1.5"	100gpm	1.5"	1.5"	1.5" internal pipe		
2"	160gpm	2"	2"	2" internal pipe		
1.5" Flanged	100gpm	1.5"	1.5"	1.5" 2 bolt oval flange		
2" Flanged	160gpm	2"	2"	2" 2 bolt oval flange		

Note: All threads conforming to ANSI B.1.20.1